BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 20 June 2002 (20.06.2002)

PCT

(10) International Publication Number WO 02/48447 A1

(51) International Patent Classification7:

D06L 1/04

(21) International Application Number: PCT/US01/26695

(22) International Filing Date: 24 August 2001 (24.08.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09/736,880

14 December 2000 (14.12.2000) US

(71) Applicant: GENERAL ELECTRIC COMPANY [US/US]; 1 River Road, Schenectady, NY 12345 (US).

(72) Inventors: PERRY, Robert, J.; 2115 Niskayuna Drive, Niskayuna, NY 12309 (US). RICCIO, Donna, Ann; 138 Haswell Road, Watervliet, NY 12189 (US). RYAN, Larry, D.; 18 Birch Glen Drive, Waterford, NY 12188 (US).

(74) Agents: HARRINGTON, Mark, F. et al., Harrington & Smith, LLP, 1809 Black Rock Turnpike, Fairfield, CT 06432-3504 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

2/48447 A1

(54) Title: SILOXANE DRY CLEANING COMPOSITION AND PROCESS

(57) Abstract: A dry cleaning composition comprising a volatile siloxane and an aminofunctional siloxane and, optionally water or acid, and a method for dry cleaning comprising contacting an article with a composition comprising a volatile siloxane and an aminofunctional siloxane.

SILOXANE DRY CLEANING COMPOSITION AND PROCESS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims rights of priority from U.S. Provisional Patent Application Serial No. 60/188,244, filed March 10, 2000.

TECHNICAL FIELD

The present invention is directed to a dry cleaning composition, more specifically, to a siloxane fluid based composition, for use in dry cleaning and to a dry cleaning process using the composition.

BACKGROUND

10.

15

Current dry cleaning technology uses perchloroethylene ("PERC") or petroleum-based materials as the cleaning solvent. PERC suffers from toxicity and odor issues. The petroleum-based products are not as effective as PERC in cleaning garments.

Cyclic siloxanes have been reported as spot cleaning solutions, see US 4,685,930, and as dry cleaning fluids in dry cleaning machines, see US 5,942,007. Other patents disclose the use of silicone soaps in petroleum solvents, see JP 09299687, and the use of silicone surfactants in super critical carbon dioxide solutions has been reported, see, for example, US 5,676,705 and Chem. Mark. Rep., 15 Dec 1997, 252(24), p. 15. Non-volatile silicone oils have also been used as the cleaning solvent requiring removal by a second washing with perfluoroalkane to remove the silicone oil, see JP 06327888.

Numerous other patents have issued in which siloxanes or organomodified silicones have been present as addenda in PERC or petroleum based dry cleaning solvents, see, for example, WO 9401510; US 4911853; US 4005231; US 4065258.

There is a continued interest in providing an additive or additives to enhance the cleaning ability of silicone based dry cleaning solvents.

SUMMARY OF THE INVENTION

5

10

15

20

In a first aspect, the present invention is directed to a dry cleaning composition, comprising a volatile siloxane and one or more aminofunctional siloxanes.

In a second aspect, the present invention is directed to a method for dry cleaning comprising contacting an article with a composition comprising a volatile siloxane and an aminofunctional siloxane.

The process of the present invention exhibits improved performance, such as for example, removal of water soluble stains from the article, for example a garment, being cleaned. The process of the present invention also exhibits improved performance for removal of soluble stains, including oil stains and grease stains.

DETAILED DESCRIPTION OF THE INVENTION

In a preferred embodiment, the composition comprises, based on 100 parts by weight ("pbw") of the composition, from greater than 90 pbw to 99.999 pbw, more preferably from 92 pbw to 99.9 pbw and even more preferably from 95 pbw to 99.5 pbw of the volatile siloxane and from 0.001 pbw to less than 10 pbw, more preferably from 0.01 pbw to 8 pbw and even more preferably from 0.1 pbw to 5 pbw of the aminofunctional siloxane or siloxanes. The volatile siloxane may be linear, branched, cyclic, or a combination thereof. The composition optionally further comprises water, preferably from 0.01 pbw to 15 pbw, more preferably from 0.1 pbw to less than 12 pbw and even more preferably from 0.2 pbw to 10 pbw of water. Preferably, the composition does not include siloxane resins or crosslinking

agents. The composition optionally further comprises acid in amounts sufficient to protonate the amino functionality of the aminofunctional silicone.

In a preferred embodiment, the water may be added as "free" water or may be delivered by an emulsion containing other components such as siloxanes, hydrocarbons, surfactants, or other suitable additives. If the water is delivered by an emulsion, the emulsion may be prepared by either homogenization of the components or by mechanically stirring the mixture.

Compounds suitable as the linear or branched, volatile siloxane solvent of the present invention are those containing a polysiloxane structure that includes from 2 to 20 silicon atoms. Preferably, the linear or branched, volatile siloxanes are relatively volatile materials, having, for example, a boiling of below about 300°C point at a pressure of 760 millimeters of mercury ("mm Hg").

In a preferred embodiment, the linear or branched, volatile siloxane comprises one or more compounds of the structural formula (I):

 $M_{2+y+2z}D_xT_yQ_z$

wherein:

10

15

M is R¹₃SiO_{1/2};

D is R2R3SiO2/2;

20 T is R4SiO_{3/2};

and Q is $SiO_{4/2}$

R¹, R², R³ and R⁴ are each independently a monovalent hydrocarbon radical; and

x and y are each integers, wherein $0 \le x \le 10$ and $0 \le y \le 10$ and $0 \le z \le 10$.

Suitable monovalent hydrocarbon groups include acyclic hydrocarbon radicals, monovalent alicyclic hydrocarbon radicals, monovalent and aromatic or fluoro containing hydrocarbon radicals. Preferred monovalent hydrocarbon radicals are monovalent alkyl radicals, monovalent aryl radicals and monovalent aralkyl radicals.

As used herein, the term "(C₁-C₆)alkyl" means a linear or branched alkyl group containing from 1 to 6 carbons per group, such as, for example, methyl, ethyl, propyl, iso-propyl, n-butyl, iso-butyl, sec-butyl, tert-butyl, pentyl, hexyl, preferably methyl.

10

15

As used herein, the term "aryl" means a monovalent unsaturated hydrocarbon ring system containing one or more aromatic or fluoro containing rings per group, which may optionally be substituted on the one or more aromatic or fluoro containing rings, preferably with one or more (C₁-C₆)alkyl groups and which, in the case of two or more rings, may be fused rings, including, for example, phenyl, 2,4,6-trimethylphenyl, 2-isopropylmethylphenyl, 1-pentalenyl, naphthyl, anthryl, preferably phenyl.

As used herein, the term "aralkyl" means an aryl derivative of an alkyl group, preferably a (C₂-C₆)alkyl group, wherein the alkyl portion of the aryl derivative may, optionally, be interrupted by an oxygen atom, such as, for example, phenylethyl, phenylpropyl, 2-(1-naphthyl)ethyl, preferably phenylpropyl, phenyoxypropyl, biphenyloxypropyl.

In a preferred embodiment, the monovalent hydrocarbon radical is a monovalent (C₁-C₆)alkyl radical, most preferably, methyl.

In a preferred embodiment, the linear or branched, volatile siloxane comprises one or more of, hexamethyldisiloxane, octamethyltrisiloxane,

decamethyltetrasiloxane, dodecamethylpentasiloxane, tetradecamethylhexasiloxane or hexadecamethylheptasiloxane or methyltris(trimethylsiloxy)silane. In a more highly preferred embodiment, the linear or branched, volatile siloxane of the present invention comprises octamethyltrisiloxane, decamethyltetrasiloxane, or dodecamethylpentasiloxane or methyltris(trimethylsiloxy)silane. In a highly preferred embodiment, the siloxane component of the composition of the present invention consists essentially of decamethyltetrasiloxane.

Suitable linear or branched volatile siloxanes are made by known methods, such as, for example, hydrolysis and condensation of one or more of tetrachlorosilane, methyltrichlorosilane, dimethyldichlorosilane, trimethylchlorosilane, or by isolation of the desired fraction of an equilibrate mixture of hexamethyldisiloxane and octamethylcyclotetrasiloxane or the like and are commercially available.

10

15

20

Compounds suitable as the cyclic siloxane component of the present invention are those containing a polysiloxane ring structure that includes from 2 to 20 silicon atoms in the ring. Preferably, the linear, volatile siloxanes and cyclic siloxanes are relatively volatile materials, having, for example, a boiling point of below about 300°C at a pressure of 760 millimeters of mercury ("mm Hg").

In a preferred embodiment, the cyclic siloxane component comprises one or more compounds of the structural formula (II):

 Π

wherein:

10

15

20

25

R⁵, R⁶, R⁷ and R⁸ are each independently a monovalent hydrocarbon group; and

a and b are each integers wherein $0 \le a \le 10$ and $0 \le b \le 10$, provided that $3 \le (a + b) \le 10$.

In a preferred embodiment, the cyclic siloxane comprises one or more of, octamethylcyclotetrasiloxane, decamethylcyclopentasiloxane, dodecamethylcyclohexasiloxane, tetradecamethylcycloheptasiloxane. In a more highly preferred embodiment, the cyclic siloxane of the present invention comprises octamethylcyclotetrasiloxane or decamethylcyclopentasiloxane. In a highly preferred embodiment, the cyclic siloxane component of the composition of the present invention consists essentially of decamethylcyclopentasiloxane.

Suitable cyclic siloxanes are made by known methods, such as, for example, hydrolysis and condensation of dimethyldichlorosilane and are commercially available.

The aminofunctional silicone comprises structural units of the formula:

R²⁰SiO_{4-f}

wherein at least one R^{20} is $-(CHR^{24})_nNR^{25}R^{26}$ where R^{24} is H or alkyl, preferably (C_1-C_8) alkyl, R^{25} is H or alkyl, preferably (C_1-C_4) alkyl, R^{26} is H, alkyl, preferably (C_1-C_8) alkyl, or $-(CHR^{27})_mNR^{28}R^{29}$ where R^{27} is H or alkyl, preferably (C_1-C_8) alkyl and R^{28} and R^{29} are each independently H or alkyl, preferably (C_1-C_4) alkyl, n is from 2 to 16, and m is from 2 to 16; and $1 \le f \le 3$.

In a preferred embodiment, the aminofunctional silicone of the present invention comprises one or more siloxanes selected from block or random

polymers and copolymers and terminally substituted aminofunctional siloxane polymers having the structural formula:

 $M^*D_xD'_yT_wT'_zM^*$ (I)

5

10

15

 (C_1-C_8) alkyl;

wherein M* is R²¹R²²R²³SiO_{1/2}, wherein each R²¹, R²² and R²³ is independently alkyl, preferably (C₁-C₈)alkyl, aryl, substituted alkyl or aryl, alkoxy, preferably (C₁-C₈)alkoxy, -(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, preferably (C₁-C₈)alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, or R²⁰, as previously defined;

D is $R^{14}_2SiO_{2/2}$, wherein each R^{14} is alkyl, preferably (C_1-C_8) alkyl or $-(CH_2)_a(CH_2CH_2C)_b(CH_2CH(CH_3)O)_cR^{15}$, wherein R^{15} is H or alkyl, preferably (C_1-C_8) alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive; D' is $R^{10}R^{11}SiO_{2/2}$, wherein R^{10} is alkyl, preferably (C_1-C_8) alkyl, aryl, or

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, preferably (C₁-C₈)alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, and R¹¹ is R²⁰, as previously defined, or polyether, alkyl, aryl, or other functional side group;

T is R¹²SiO₃/₂, wherein R¹² is alkyl or aryl, preferably (C₁-C₈)alkyl or -(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, preferably

- T' is R¹³SiO_{3/2}, wherein R¹³ is alkyl, preferably (C₁-C₈)alkyl, aryl, or -(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, preferably (C₁-C₈)alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, and R¹¹ is R²⁰, as previously defined, or polyether, alkyl, aryl, or other functional side group;
- 25 and w, x, y and z are integers such that $0 \le w \le 40$, $0 \le x \le 500$, $0 \le y \le 50$, $0 \le z \le 40$.

Compounds suitable as the aminofunctional silicone of the present invention include, but are not limited to, aminoethylaminopropyl linear graft copolymer, aminoethylaminopropyl branched graft copolymer, aminoethylaminopropyl terminal linear polymers, aminoethylaminoisobutyl branched graft copolymers, aminoethylaminoisobutyl linear graft copolymers, aminoethylaminoisobutyl terminal linear polymers, aminopropyl graft linear copolymers, aminopropyl terminally substituted linear polymer, aminoethylaminopropyl linear graft terpolymer with ethylene oxide-propylene oxide side chain, and the like.

In a preferred embodiment, the aminofunctional silicone of the present invention is an aminoalkyl substituted siloxane compound which may or may not be polymeric, wherein the aminoalkyl substituent is terminally substituted, substituted on a repeating unit, or both terminally substituted and substituted on a repeating unit, of a polymeric or copolymeric species, such as an aminoalkyl terminally substituted linear siloxane, an aminoalkyl terminally substituted branched siloxane, a linear siloxane with aminoalkyl substitution on chain, a branched siloxane with an aminoalkyl substitution on chain, an aminoalkyl linear graft copolymer, an aminoalkyl branched graft

copolymer, an aminoalkyl linear graft terpolymer, or an aminoalkyl branched

10

20

25

graft terpolymer.

In one preferred embodiment, each R^{21} , R^{22} , R^{23} and R^{10} is $(C_1\text{-}C_8)$ alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, and w and z are 0. In another preferred embodiment, each R^{21} , R^{22} , R^{23} , R^{10} and R^{12} is $(C_1\text{-}C_8)$ alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, R^{13} is a polyether, and w is 0. In another preferred embodiment, each R^{21} , R^{22} , R^{23} , R^{10} and R^{15} is $(C_1\text{-}C_8)$ alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, and w is > 0. In another preferred embodiment, each R^{21} , R^{22} , R^{10} and R^{14} is $(C_1\text{-}C_8)$ alkyl, R^{23} is $(CH_2)NH_2$, w, y and z are 0, and x is from 2 to 100, preferably 2 to 10, preferably x is 2 or 10.

In a preferred embodiment, the dry cleaning composition of the present invention further comprises a minor amount, preferably, less than 50 pbw per 100 pbw of the composition, more preferably, less than 10 pbw per 100 pbw of the composition, of one or more non-siloxane fluids. Suitable non-siloxane fluids include aqueous fluids, such as, for example, water, and organic fluids, for example, hydrocarbon fluids and halogenated hydrocarbon fluids.

5

10

15

20

25

In a preferred embodiment, the dry cleaning composition of the present invention further comprises a minor amount, preferably less than 10 pbw, more preferably less than 8 pbw, even more preferably less than 5 pbw per 100 pbw of the composition, of one or more surfactants. Suitable surfactants include organic surfactants such as anionic, nonionic, cationic and amphoteric surfactants, and silicone surfactants.

An article, such as for example, a textile or leather article, typically, a garment, is dry cleaned by contacting the article with the composition of the present invention. In a preferred embodiment, the articles to be cleaned include textiles made from natural fibers, such as for example, cotton, wool, linen and hemp, from synthetic fibers, such as, for example, polyester fibers, polyamide fibers, polypropylene fibers and elastomeric fibers, from blends of natural and synthetic fibers, from natural or synthetic leather or natural or synthetic fur.

The article and dry cleaning composition are then separated, by, for example, one or more of draining and centrifugation. In a preferred embodiment, separation of the article and dry cleaning composition is followed by the application of heat, preferably, heating to a temperature of from 15°C to 120°C, preferably from 20°C to 100°C, or reduced pressure,

preferably, a pressure of from 1 mm Hg to 750 mm Hg, or by application of both heat and reduced pressure, to the article.

Testing for water soluble stain removal was accomplished using fabric swatches supplied by the International Fabricare Institute ("IFI") (Silver Spring, MD) that contained a water soluble dye. The color change of a swatch of this material was measured by a Minolta CR-300[®] Colorimeter using the Hunter Color Number difference calculations. The larger the change in Hunter Color Number (AE), the greater the dye removal and the more efficient the cleaning.

The following examples are to illustrate the invention and are not to be construed as limiting the claims.

EXAMPLES

. 10

20

Testing procedure: Circular swatches (from IFI) containing a water soluble dye were measured by the colorimeter, and the initial color values for L, a and b (as defined by the Hunter Color Numbers) were recorded. The fabric swatches were then placed in vials containing the cleaning composition of the present invention, and the vial was shaken for 10 minutes at ambient temperature. The fabric swatch was removed and allowed to drip dry for 2 to 5 seconds, then placed on absorbent toweling and allowed to air dry for 16 to 24 hours. A second reading of each fabric swatch was taken and the color difference (ΔE) was determined using the following formula:

$$\Delta E = [(L_1-L_2)^2 + (a_1-a_2)^2 = (b_1-b_2)^2]^{1/2}$$

This color difference represents the relative amount of cleaning, with the higher ΔE indicative of better cleaning performance.

Example 1 - Aminofunctional Siloxanes

A cleaning composition according to the present invention containing a cyclic siloxane (D₅) and one or more aminofunctional siloxanes was made. Fabric swatches were cleaned using the above procedure, and the color difference was measured to determine the effectiveness of the cleaning composition. A solution of cyclic siloxane (D₅) without a surfactant was used as a control.

5

Amino-	Milli equiv.	Aminofunctional Siloxane Structure
functional	amine/g	
Siloxane	(approx.)	
Α	0.7	Aminoethylaminopropyl linear graft copolymer
В	0.55	Aminoethylaminopropyl branched graft copolymer
С	0.35	Aminoethylaminopropyl linear graft terpolymer with ethylene oxide-propylene oxide side chain
D	0.46	Aminoethylaminopropyl reactive branched graft copolymer
E	0.6	Aminoethylaminopropyl reactive linear graft copolymer
F	0.7	Aminoethylaminopropyl branched graft copolymer
G	5.1	Aminopropyl terminally substituted linear polymer
Н	2.0	Aminopropyl terminally substituted linear polymer

Table 1 – Aminofunctional Siloxanes in D₅

Exp. No.	D ₅ (g)	Aminofunctional Siloxane	Amount (g)	ΔΕ
1	14.85	A	.15	1.7
2	14.25	A	.75	4.2
3	14.85	D	.15	1.9
4	14.25	D	.75	2.3
5	14.85	В	.15	1.6
6	14.25	В	.75	1.7
7	14.85	C	.15	3.5
8	14.25	С	.75	13.2
9	14.85	E	.15	2.0
10	14.25	E	.75	1.9
11	14.85	F	.15	1.8
12	14.25	F	.75	1.7
13	14.85	G	.15	6.3
14	14.25	G	.75	14.7
15	14.85	H	.15	2.9
16	14.25	H	.75	11.0
Control-1	15.00	-	-	1.9

Table 1 shows that some aminofunctional siloxanes enhance the cleaning and dye removal of the base cyclic siloxane (D_5) solvent.

Table 2 – Aminofunctional Siloxanes in D_5 with Water Added

Exp. No.	D ₅ (g)	Aminofunctional Siloxane	Amount (g)	Water (g)	ΔΕ
17	14.25	C	0.60	0.15	27.0
18	14.25	С	0.15	0.60	14.4
19	14.7	С	0.15	0.15	11.3
20	14.25	G	0.60	0.15	40.4
21	14.25	G	0.15	0.60	37.1
22	14.7	G ·	0.15	0.15	39.9
23 -	14.25	D	0.60	0.15	12.3
24	14.25	D	0.15	0.60	5.4
25	14.7	D	0.15	0.15	3.4
26	14.25	A	0.60	0.15	12.0
27	14.25	A	0.15	0.60	6.0
28	14.7	A	0.15	0.15	3.5.
29	14.25	H	0.60	0.15	34.0
30	14.25	Н	0.15	0.60	20.6
31	14.7	H	0.15	0.15	24.8
Control-1	15.00				1.9
Control-2	14.85	•	• 4,000	0.15	2.2
Control-3	14.40	-	_	0.60	9.5

Table 2 shows that the presence of water enhanced the cleaning action of the amino silicones.

Example 3 - Aminofunctional Siloxanes in D₅ with Acid Added

Exp.	D ₅ (g)	Aminofunctional Siloxane	Amt (g)	Water (g)	Acetic Acid	Delta E
32	14.85	C	0.15		5 micro L	2.65
33	14.25	С	0.75	-	20 micro L	5.93
34	14.25	С	0.6	0.15	15 micro L	6.60
35	14.25	С	0.15	0.6	5 micro L	30.31
36	14.7	С	0.15	0.15	5 micro L	6.55
37	14.85	G	0.15	-	45 micro L	23.36
38	14.25	G	0.75	•	225 micro L	30.73
-39	14.25	G	0.6	0.15	180 micro L	30.69
40	14.25	G	0.15	0.6	45 micro L	31.98
41	14.7	G	0.15	0.15	45 micro L	37.69
42	14.85	H	0.15	-	20 micro L	23.41
43	14.25	H.	0. <i>7</i> 5	• ,	90 micro L	30.71
44	14.25	Н	0.6	0.15	75 micro L	33.22
45	14.25	Н	0.15	0.6	20 micro L	33.20
46	14.7	H	0.15	0.15	20 micro L	32.26
47	14.85	Α.	0.15	-	10 micro L	6.14
48	14.25	A	0.75	•	35 micro L	4.66
49	14.25	A	0.6	0:15	30 micro L	4.70
50	14.25	A	0.15	0.6	10 micro L	3.01
51	14.7	Α	0.15	0.15	10 micro L	4.15
Control 4	15.0	•	-	•	10 micro L	2.68
Control 5	14.85	•	-	0.15	10 micro L	2.11
Control 6	14.85	•	-	0.15	-	2.07

Table 3 shows that quaternized aminofunctional siloxanes also enhance cleaning of silicone solvents when compared to just the solvent, or solvent and water, acid or both.

Table 4 - Aminofunctional Emulsions

Exp.	D ₅ (g)	Emulsion	Amt (g)	% solids	Delta E
- 52	14.25	1	0.75	20	41.6
53	14.25	2	0.75	20	40.2
54	14.25	3	0.75	35	43.7
55	14.25	4	0.75	35	38.4

Emulsion	Components of Emulsion
1	2 alkyl aryl ethoxy alcohol surfactants, quaternary ammonium
	salt, and a curable amino siloxane
2	2 ethoxy alkyl alcohol surfactants, ethoxylated alcohol surfactant,
	and a commercially available aminofunctional emulsion (with A)
3	Quaternary ammonium salt, ethoxylated alcohol surfactant and
	commercially available curable trialkoxyaminosilane emulsion
4	Ethoxylated dialkyl ammonium salt, alkyl aryl ethoxy alcohol,
	and a curable trialkoxyaminosilane emulsion

The surfactants used in the emulsions are known in the art and are commercially available as such trade names, for example, as Triton, Tergitol, Varisoft and the like.

Table 4 illustrates that emulsions of aminofunctional siloxanes and aminofunctional silanes, in conjunction with organic surfactants, are also effective at cleaning water soluble stains.

The present invention exhibits improved performance of dry cleaning agents for stain removal, particularly water soluble stains, through the addition of an aminofunctional silicone, and optionally water, acid or organic surfactants.

10

15

20

CLAIMS:

- 1. A dry cleaning composition, comprising a volatile cyclic, linear or branched siloxane, or combination thereof, and one or more aminofunctional siloxanes.
- 2. The composition of Claim 1, comprising from about 90 to about 99.999 parts by weight of the volatile siloxane and from about 0.001 to less than 10 parts by weight of the aminofunctional siloxane or siloxanes.
- 3. The composition of Claim 2, further comprising from about 0.01 to about 15 parts by weight of water.
- 4. The composition of Claim 1, wherein the aminofunctional siloxane comprises structural units of the formula:

R²⁰SiO_{4-f}

wherein at least one R^{20} is $-(CHR^{24})_nNR^{25}R^{26}$ where R^{24} is H or alkyl, preferably (C_1-C_8) alkyl, R^{25} is H or alkyl, R^{26} is H, alkyl, or $-(CHR^{27})_mNR^{28}R^{29}$ where R^{27} is H or alkyl, and R^{28} and R^{29} are each independently H or alkyl, n is from 2 to 16, and m is from 2 to 16; and $1 \le f \le 3$.

5. The composition of Claim 4, wherein the aminofunctional silicone comprises one or more siloxanes selected from block or random polymers and copolymers and terminally substituted aminofunctional siloxane polymers having the structural formula:

$$M^*D_xD'_yT_wT'_zM^*$$
 (I)

wherein M^* is $R^{21}R^{22}R^{23}SiO_{1/2}$, wherein each R^{21} , R^{22} and R^{23} is independently alkyl, aryl, substituted alkyl or aryl, alkoxy,

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, or R²⁰, as previously defined;

D is R¹⁴₂SiO_{2/2}, wherein each R¹⁴ is alkyl or
-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2
to 8 inclusive, b and c are each from 0 to 20 inclusive;
D' is R¹⁰R¹¹SiO_{2/2}, wherein R¹⁰ is alkyl, aryl, or

5

· 10

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, and R¹¹ is R²⁰, as previously defined, or polyether, alkyl, aryl, or other functional side group; T is R¹²SiO₃/₂, wherein R¹² is alkyl or aryl, or

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_c R^{15} , wherein R^{15} is H or alkyl;

T' is R¹³SiO₃/2, wherein R¹³ is alkyl, aryl, or $-(CH_2)_a(CH_2CH_2C)_b(CH_2CH(CH_3)O)_cR^{15}$, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, and R¹¹ is R²⁰, as previously defined, or polyether, alkyl, aryl, or other functional side group; and w, x, y and z are integers such that $0 \le w \le 40$, $0 \le x \le 500$, $0 \le y \le 50$, $0 \le z \le 40$.

- 6. The composition of Claim 5, wherein each R^{21} , R^{22} , R^{23} and R^{10} is (C₁-C₈)alkyl, R^{11} is (CH₂)_nNH(CH₂)_mNH₂, and w and z are 0.
 - 7. The composition of Claim 5, wherein each R^{21} , R^{22} , R^{23} , R^{10} and R^{12} is (C_1-C_8) alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, R^{13} is a polyether, and w is 0.
 - 8. The composition of Claim 5, wherein each R^{21} , R^{22} , R^{23} , R^{10} and R^{15} is (C_1-C_8) alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, and w is > 0.

- 9. The composition of Claim 5, wherein each R^{21} , R^{22} , R^{10} and R^{14} is (C₁-C₈)alkyl, R^{23} is (CH₂)NH₂, w, y and z are 0, and x is from 2 to 100.
- 10. The composition of Claim 9, wherein x is from 2 to 10, preferably x is 2 or 10.
 - 11. The composition of Claim 10, wherein x is 2 or 10.
- 12. The composition of Claim 1, wherein the linear or branched, volatile siloxane comprises one or more compounds of the structural formula:

 $M_{2+y+2z}D_xT_yQ_z$

wherein:

10 M is R¹₃SiO_{1/2};

D is R2R3SiO2/2;

T is $R4SiO_{3/2}$;

and Q is SiO_{4/2}

15

R¹, R², R³ and R⁴ are each independently a monovalent hydrocarbon radical; and

x and y are each integers, wherein $0 \le x \le 10$ and $0 \le y \le 10$ and $0 \le z \le 10$.

13. The composition of Claim 1, wherein the cyclic siloxane component comprises one or more compounds of the structural formula:

wherein:

15

20

R⁵, R⁶, R⁷ and R⁸ are each independently a monovalent hydrocarbon group; and

- a and b are each integers wherein $0 \le a \le 10$ and $0 \le b \le 10$, provided that $3 \le (a + b) \le 10$.
 - 14. A method for dry cleaning an article, comprising contacting the article with a composition comprising a cyclic, linear or branched siloxane and one or more aminofunctional siloxanes.
- 15. The method of Claim 14, wherein the aminofunctional siloxane comprises structural units of the formula:

R²⁰_fSiO_{4-f}

wherein at least one R^{20} is $-(CHR^{24})_nNR^{25}R^{26}$ where R^{24} is H or alkyl, preferably (C_1-C_8) alkyl, R^{25} is H or alkyl, R^{26} is H, alkyl, or $-(CHR^{27})_mNR^{28}R^{29}$ where R^{27} is H or alkyl, and R^{28} and R^{29} are each independently H or alkyl, n is from 2 to 16, and m is from 2 to 16; and $1 \le f \le 3$.

16. The method of Claim 15, wherein the aminofunctional silicone comprises one or more siloxanes selected from block or random polymers and copolymers and terminally substituted aminofunctional siloxane polymers having the structural formula:

20

$M*D_xD'_yT_wT'_zM*$

(I)

wherein M* is R²¹R²²R²³SiO_{1/2}, wherein each R²¹, R²² and R²³ is independently alkyl, aryl, substituted alkyl or aryl, alkoxy,

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, or R²⁰, as previously defined;

D is R142SiO2/2, wherein each R14 is alkyl or

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive;

10 D' is $R^{10}R^{11}SiO_{2/2}$, wherein R^{10} is alkyl, aryl, or

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, and R¹¹ is R²⁰, as previously defined, or polyether, alkyl, aryl, or other functional side group;

T is R12SiO3/2, wherein R12 is alkyl or aryl, or

15 $-(CH_2)_a(CH_2CH_2C)_b(CH_2CH(CH_3)O)_cR^{15}$, wherein R^{15} is H or alkyl;

T' is $R^{13}SiO_{3/2}$, wherein R^{13} is alkyl, aryl, or

-(CH₂)_a(CH₂CH₂O)_b(CH₂CH(CH₃)O)_cR¹⁵, wherein R¹⁵ is H or alkyl, a is from 2 to 8 inclusive, b and c are each from 0 to 20 inclusive, and R¹¹ is R²⁰, as previously defined, or polyether, alkyl, aryl, or other functional side group;

and w, x, y and z are integers such that $0 \le w \le 40$, $0 \le x \le 500$, $0 \le y \le 50$, $0 \le z \le 40$.

17. The method of Claim 16, wherein each R^{21} , R^{22} , R^{23} and R^{10} is (C_1-C_8) alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, and w and z are 0.

18. The method of Claim 16, wherein each R^{21} , R^{22} , R^{23} , R^{10} and R^{12} is (C_1-C_8) alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, R^{13} is a polyether, and w is 0.

- 19. The method of Claim 16, wherein each R^{21} , R^{22} , R^{23} , R^{10} and R^{15} is (C_1-C_8) alkyl, R^{11} is $(CH_2)_nNH(CH_2)_mNH_2$, and w is > 0.
- 20. The composition of Claim 16, wherein each R^{21} , R^{22} , R^{10} and R^{14} is (C_1-C_8) alkyl, R^{23} is $(CH_2)NH_2$, w, y and z are 0, and x is from 2 to 100.

5

INTERNATIONAL SEARCH REPORT

Inter 1al Application No PCT/US 01/26695

			PCT/US 01/2	0695
A. CLASSII	FICATION OF SUBJECT MATTER D06L1/04	., 		
116 /	, , , , , , , , , , , , , , , , , , ,			
According to	International Patent Classification (IPC) or to both national class	sification and IPC		
	SEARCHED			
Minimum do	cumentation searched (dassification system followed by classification syst	cation symbols)		
Dogumentet	tion searched other than minimum documentation to the extent th	at such documents are Inc	tuded in the fields sea	ched
		<i>.</i> ·		
Electronic d	ata base consulted during the International search (name of data	a base and, where practice	al, search terms used)	·
WPI Da	ta, EPO-Internal, PAJ			
C DC0184	ENTS CONSIDERED TO BE RELEVANT	· · · · · · · · · · · · · · · · · · ·		
	Citation of document, with indication, where appropriate, of the	relevant passages		Relevant to claim No.
Category *	Citation of document, with situation, where appropriate, of the			
Y	EP 1 043 443 A (GEN ELECTRIC) 11 October 2000 (2000-10-11)	e e		1-20
	page 4, line 41 - line 44; cla	ims		
	8,9,11,12; example 3	· · · · · · · · · · · · · · · · · · ·		
Υ	EP 0 375 028 A (PROCTER & GAMBI 27 June 1990 (1990-06-27)		1 m	1-20
sast,	page 5, line 1 - line 20; clair	ns 1,9,10	i garan da da gaga da 🖟	
: '				•
			·	
	·		}	
· .	4	•		
·				
			· · · · · · · · · · · · · · · · · · ·	
,				
<u> </u>			·	
Furt	ther documents are listed in the continuation of box C.	X Patent fam	ily members are listed i	n annex.
• Special ca	ategories of cited documents:	"T" later document o	oublished after the inte	mational filing date
A docum	ent defining the general state of the art which is not	or priority date cited to unders	and not in conflict with tand the principle or the	the application but
consid	dered to be of particular relevance document but published on or after the international	Invention "X" document of par	ticular relevance: the c	aimed Invention
filing		cannot be cons	dered novel or cannot	be considered to current is taken alone
which	ent which may into woods on promy callings of is cited to establish the publication date of another in or other special reason (as specified)	"Y" document of par	ticular relevance; the c sidered to involve an inv	laimed invention
O docum	ent referring to an oral disclosure, use, exhibition or	document is co	mbined with one or mo mbination being obvious	re other such docu-
PDF docum	means ent published prior to the international filling date but han the priority date claimed	in the ext.	per of the same patent	
Date of the	actual completion of the international search	Date of malling	of the international sea	arch report
1	5 March 2002	27/03	/2002	
Namo	mailing address of the ISA	Authorized offic	er	
Name and	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk			
	Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Facc (+31-70) 340-3016	Saund	ers, T	

INTERNATIONAL SEARCH REPORT

Inter 1al Application No PCT/US 01/26695

					,
Patent document dted in search report		Publication date		Patent family member(s)	Publication date
EP 1043443	Α	11-10-2000	US	6310029 B1	30-10-2001
*1			EP	1043443 A1	11-10-2000
			JP	2000313900 A	14-11-2000
· <u></u>		·. 	US	2001034912 A1	01-11-2001
EP 0375028	A	27-06-1990	US	4911853 A	27-03-1990
			ΑÜ	638440 B2	01-07-1993
			AU	4712889 A	28-06-1990
			BR	8906599 A	04-09-1990
			CA	2004163 A1	21-06-1990
			ΕP	0375028 A2	27-06-1990
			JP	2259159 A	19-10-1990
			KR	9700322 B1	08-01-1997
		*	MX	165880 B	08-12-1992

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.